

HD FLOW™ Pro Wireless Multimedia Kit




Features

- Full HD 1080p (60Hz) (24/30/60 fps) and passive 3D signal flow, ideal for ultra-fast signal streaming
- Long range, high-quality streaming up to 131ft (40m) with no reduction of picture quality
- Multicast up to four HD Flow™ Pro Wireless Receivers*
- Instant real-time transmission of Full HD media
- Transmits through walls and ceilings for multi-room streaming capability
- The HD Flow™ Pro (802.11n) private network resists interference and network sharing from nearby wireless routers
- Built-in IR does not require line-of-sight placement to control source devices such as DVR/set-top box, satellite box, Blu-ray®/DVD player, media server, VCR, game console
- Plug and play setup requires no software or driver installation


* Requires additional receiver units



- 1 Confirms that the 802.11n private network has been set up and is ready for Full HD 1080p and passive 3D wireless signal streaming
- 2 Plug in up to five (5) AV source devices and easily switch between them with the included remote control
- 3 Four (4) output port options available — ideal for virtually any output device
- 4 Built-in IR controls source devices without need for line-of-sight device placement
- 5 Small footprint makes it easy to fit the HD Flow™ Pro units into any application



Transmitter back



Receiver back

When running cables is not an option, stream HD content wirelessly with the HD Flow™ Pro Wireless Multimedia Kit. With five (5) inputs and the ability to multicast to up to four (4) displays, this wireless workhorse streams Full HD 1080p and passive 3D signals up to 131ft (40m) to an HDTV, projector or any other display. For new installations and retrofits alike, this kit is a project-saving tool for professional AV integrators for both commercial and residential applications.

HDS200	HD Flow™ Pro Wireless Multimedia Kit
HDS200-2	HD Flow™ Pro Wireless Multimedia Kit - Multicast: Two Receivers
HDS200-3	HD Flow™ Pro Wireless Multimedia Kit - Multicast: Three Receivers
HDS200-4	HD Flow™ Pro Wireless Multimedia Kit - Multicast: Four Receivers



Inputs (Transmitter)

- 2 x HDMI
- 1 x Composite Video & Stereo Audio
- 1 x VGA: High Density 15-Pin D-Sub (RGB)
- AUDIO IN: - 1 x 3.5mm Audio Jack
- 1 x Stereo RCA Audio Jack
- 1 x IR Port
- 1 x LAN (Ethernet): RJ45 Jack



Outputs (Receiver)

- 1 x HDMI
- 1 x Composite Video & Stereo Audio
- 1 x Component Video
- 1 x USB Type A (Female)
- AUDIO OUT: - 1 x 3.5mm Audio Jack
- 1 x Stereo RCA Audio Jack
- 1 x IR Port
- 1 x LAN (Ethernet): RJ45 Jack

Product Specifications

Video Input (Transmitter)	- 2 x HDMI up to 1080p (60Hz), 1920x1080 - 1 x Composite - 1 x YPbPr Component	Audio Output	- 1 x 3.5mm Audio Jack - 1 Stereo RCA Audio Jack (Receiver)	IR Flasher	- 3 IR Flashers
Video Output (Receiver)	- 1 x HDMI up to 1080p (60Hz), 1920x1080 - 1 x Composite - 1 x YPbPr Component	Power	- Voltage: 120V AC, 60Hz - Consumption: 12V DC, 2A	IR Extender	- 1 IR Extender
Encoding	- H.264 Baseline Profile with Level 4.2 - HDCP Compliant	Video Resolution	- 480i/p, 720p, 1080i and 1080p (24/30/60fps)	Remote Control	- 1 x with 16 Keys
Wireless Connection	- Supporting IEEE 802.11n: OFDM	Video Streaming	- < 30ms Latency	LEDs	- Port ID 4 x LED on Transmitter; 3 x LED on Receiver - Power On 1 x LED (Transmitter and Receiver) - Link 1 x LED (Transmitter and Receiver)
Wire Connection	- RJ45 LAN Port - Direct Connection (LAN Cable)	Frequency	- 5.15-5.25GHz	Color	- Black
LAN	- 1 x LAN Port (Transmitter and Receiver) - 10/100 Base	LAN Connection	- 10/100 Base	Housing Case	- Plastic
USB	- 1 x USB Type A Female (Receiver)	Range	- 131ft (40m)	Unit Specifications	- Dimensions (W x H x D): 1.25" x 7.63" x 4.5" (31 x 193 x 114mm) - Unit Weight: 1.36lb (0.62kg) - Unit Weight w/accessories: 2.32lb (1.05kg)
Audio	- 2 Ch. Linear PCM, - Analog, 48kHz 16-bit ADC	Broadcast	- 1 Transmitter to 4 Receivers*	Master Pack Specifications	- Master Pack Qty: 9ea - Dimensions (W x H x D): 20" x 9.4" x 15.6" (508 x 239 x 396mm) - Ship Weight: 31.52lb (14kg)
Audio Input	- 1 x 3.5mm Audio Jack, - 1 Stereo RCA Audio Jack (Transmitter)	Security	- 802.1x, 802.11i, WPA2, WPA and WEP 64/128 TKIP AES		
		Antenna Type	- 2 x Internal Antenna (Transmitter and Receiver) - MIMO Interface		

* Multicast models available (HDS200-2,-3,-4)

Package Specifications

	PACKAGE SIZE (L x W x H)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
HDS-200	6.53" x 5" x 8.46" (166 x 127 x 215mm)	4.7lb (2.13kg)	735029291398	1 x Transmitter, 1 x Receiver, 2 x Stand, 1 x Remote control, 1 x IR Flasher, 1 x IR Extender, 1 x Component adapter, 2 x Power adapter	1
HDS200-2	10" x 10" x 10" (254 x 254 x 254mm)	6.4lb (2.9kg)	735029291626	1 x Transmitter, 2 x Receiver, 3 x Stand, 2 x Remote control, 1 x IR Flasher, 1 x IR Extender, 1 x Component adapter, 3 x Power adapter	1
HDS200-3	10.625" x 9.75" x 13" (270 x 248 x 330mm)	8.3lb (3.18kg)	735029291633	1 x Transmitter, 3 x Receiver, 4 x Stand, 3 x Remote control, 1 x IR Flasher, 1 x IR Extender, 1 x Component adapter, 4 x Power adapter	1
HDS200-4	10.625" x 9.75" x 13" (270 x 248 x 330mm)	10.1lb (4.18kg)	735029291640	1 x Transmitter, 4 x Receiver, 5 x Stand, 4 x Remote control, 1 x IR Flasher, 1 x IR Extender, 1 x Component adapter, 5 x Power adapter	1

Accessories

	EC-HD015F: 1.5ft (.5m) High Speed HDMI Cable with Ethernet		EC-HD025F: 2.5ft (.75m) High Speed HDMI Cable with Ethernet		EC-HD03F: 3ft (1m) High Speed HDMI Cable with Ethernet		HDS200-R: HD Flow™ Pro Wireless Multimedia Receiver**		HDS-ASE: Wireless Tx/Rx Security Enclosure for use with HD Flow™ and HD Flow™ Pro Models		HDS-S: Wall Shelf for use with HD Flow models		HDS-IRE: IR Extender
--	---	--	--	--	---	--	---	--	--	--	---	--	--------------------------------

** Requires transmitter and system programming for operation.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including wireless devices, interactive devices, flat panel mounts, projector mounts, carts/stands, furniture, cables, screen cleaners and a full assortment of accessories.